

**Dekafix
DEK 5 FW 201-250**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com



The dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a large range of ready-printed markers. Strips for fast installation in one work step. The printing is easy to read, rich in contrast, and is available in five widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Connector markers, suitable for all Weidmüller cable connectors
- Available as blank cards, MultiCard or as cards with standard printing

General ordering data

Type	DEK 5 FW 201-250
Order No.	0473460201
Version	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00 Weidmueller, White
GTIN (EAN)	4008190014520
Qty.	500 pc(s).

Data sheet

**Dekafix
DEK 5 FW 201-250**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

Dimensions and weights

Length	5 mm	Width	5 mm
Net weight	0.04 g		

General data

Application/manufacture	Weidmueller	Colour	White
Colour of printing	Black	Length	5 mm
Material	Polyamide 66	Material colour according to resistance code	9
Operating temperature range, max.	100 °C	Operating temperature range, min.	-40 °C
Orientation of print	horizontal	Printed characters	Numbers
Printing method	MC Laser	UL 94 flammability rating	V-2
Width	5 mm		

Connector markers

Pitch in mm (P)	5 mm
-----------------	------

Classifications

ETIM 3.0	EC000761	ETIM 4.0	EC000761
ETIM 5.0	EC000761	ETIM 6.0	EC000761
UNSPSC	30-21-18-07	eClass 5.1	27-14-11-37
eClass 6.2	27-14-11-37	eClass 7.1	27-14-11-37
eClass 9.0	27141137		

Approvals

Approvals



ROHS	Conform
------	---------